

### **AMENDMENTS TO THE CLAIMS**

Claim 1 (Currently Amended): A liquid supply method that prepares a solution by continuously supplying a supply liquid to a primary fluid that is circulating in a primary fluid circulation tube, that uses a liquid supply apparatus that comprises:

a supply section that delivers the supply liquid; and

a supply liquid circulation tube formed in a hollow fiber shape that causes the supply liquid to flow from the supply section to the primary fluid circulation tube, the internal diameter of the supply liquid circulation tube being between 0.01 and 1 mm, ~~wherein~~

when the supply solution is supplied from the supply section to the primary fluid circulation tube via the supply liquid circulation tube, a pressure P1 of the supply liquid in the supply section and a pressure P2 of the primary fluid in the primary fluid circulation tube always satisfy the formula  $P1 - P2 > 0$ ;

P1/P2 is 1.01 to 10;

P1 is controlled so as to maintain a constant level;

the primary fluid is ultrapure water;

the supply liquid is an electrolytic aqueous solution; and

an electrolyte concentration of the primary fluid to which the supply liquid is supplied is between 0.00001 and 0.1 percent by mass,

wherein a supply quantity of the supply liquid can be determined without performing feedback control.

Claims 2-5: (Canceled).

Claim 6 (Previously Presented): The liquid supply method according to claim 1, wherein a supply quantity of the supply liquid is between 0.001 and 10 cm<sup>3</sup>/ minute.

Claim 7 (Previously Presented): The liquid supply method according to claim 6, wherein a ratio X/Y between a flow quantity X of the supply solution and a flow rate Y of the primary fluid is between 1/1000000 and 1/1000.

Claim 8 (Currently Amended): A liquid supply apparatus that prepares a solution by continuously supplying a supply liquid to a primary fluid that is circulating in a primary fluid circulation tube, the liquid supply apparatus comprising:

a supply section that delivers the supply liquid; and

a supply liquid circulation tube formed in a hollow fiber shape that causes the supply liquid to flow from the supply section to the primary fluid circulation tube, the internal diameter of the supply liquid circulation tube being between 0.01 and 1 mm, ~~wherein~~

when the supply solution is supplied from the supply section to the primary fluid circulation tube via the supply liquid circulation tube, a pressure P1 of the supply liquid in the supply section and a pressure P2 of the primary fluid in the primary fluid circulation tube always satisfy the formula  $P1 - P2 > 0$ ;

P1/P2 is 1.01 to 10;

P1 is controlled so as to maintain a constant level;

the primary fluid is ultrapure water;

the supply liquid is an electrolytic aqueous solution; and

an electrolyte concentration of the primary fluid to which the supply liquid is supplied is between 0.00001 and 0.1 percent by mass,

wherein a supply quantity of the supply liquid can be determined without performing feedback control.

Claim 9: (Canceled)

Claim 10 (Previously Presented): The liquid supply method according to claim 1, wherein a ratio X/Y between a flow quantity X of the supply solution and a flow rate Y of the primary fluid is between 1/1000000 and 1/1000.

Claim 11 (Canceled)

Claim 12 (Previously Presented): The liquid supply method according to claim 8, wherein a ratio X/Y between a flow quantity X of the supply solution and a flow rate Y of the primary fluid is between 1/1000000 and 1/1000.

Application No. 10/574,954  
Amendment dated September 30, 2010  
After Final Office Action of March 31, 2010

4

Docket No.: 80360(47762)

Claim 13. (Canceled).